

PROJECT:	TYPE:
LOCATION:	CAT:

Description

Flexible LED linear lighting that mimics the look of neon in a brighter, longer lasting format that consumes less power

Features

- PU construction provides excellent UV, salt water, chlorine, high temperature, and impact resistance
- Weatherproof IP67 outdoor rating
- Vertical flexibility (relative to light source)
- Quick-ship skus or special order options

Mounting


Aluminum channel or mounting clips

Applications

Outlining building facades and roof-lines, columns and pillars, coves and eaves

Warranty

5 Years




Technical Information




Input Voltage	24V DC Constant Voltage				
Max Current	0.416A per meter / 0.127A per foot				
Max Power	10W per meter / 3.05W per foot				
Color	Ultra Warm White	Warm White	White	Bright White	Cool White
CCT/nm	2700K	3000K	4000K	5000K	6000K
Lumens	246Lm/ft	250Lm/ft	259Lm/ft	263Lm/ft	268Lm/ft
CRI	80+				
Cut Increments	50mm (1.96")				
Max Run	10 meters (32.8 feet) interconnected				
Dimming	10-100% with most TRIAC or ELV dimmers*; 0-10V Dimming capable				
Ambient Temp	-30°C (-22°F) to 80°C (176°F)**				
Rating	cETLus Listed; Indoor/Outdoor; IP67				
Rated Life	50,000 Hours				

*Minimum loads may apply. Per the NEC, switched wall outlets cannot be used with wall dimmers. **Do not install during inclement weather or extreme temperature conditions (i.e. -25°C (-13°F) and below)


Side Profile



Top Profile



Photometrics For additional photometric information and IES files, please visit PrizmLighting.com




Temperature	3000K
Total Lumens	Lm
CRI	<
Beam Angle	0°

Quick-Ship Order Information

FIXTURE	ITEM NUMBER	FIXTURE	ITEM NUMBER
4FT NEOFLUX V-SERIES WARM WHITE 3000K	PZM-NFV-4-WW	8FT NEOFLUX V-SERIES WARM WHITE 3000K	PZM-NFV-8-WW
4FT NEOFLUX V-SERIES BRIGHT WHITE 5000K	PZM-NFV-4-WH	8FT NEOFLUX V-SERIES BRIGHT WHITE 5000K	PZM-NFV-8-WH
ACCESSORY		ITEM NUMBER	
4FT ALUMINUM CHANNEL FOR NEOFLUX V-SERIES		PZM-NFV-CHAN-4	
1FT 2PIN JUMPER CABLE FOR NEOFLUX SINGLE COLOR		PZM-NF-2JUMP1	
10FT 2PIN JUMPER CABLE FOR NEOFLUX SINGLE COLOR		PZM-NF-2JUMP10	
BAG OF 2 MOUNTING BRACKET FOR NEOFLUX V-SERIES		PZM-NFV-CLIPS	
BAG OF 10 END CAPS FOR NEOFLUX V-SERIES		PZ-NFV-END	

Special Order Information

Please allow 12-16 weeks for special order items



Recommended Power Supplies

SERIES	RATED POWER AVAILABLE
LED-DR Series	30W, 60W, 96W, 150W
ADPT-DRJ Series	30W, 60W, 96W